GORILLA GLUE GUIDE

		The multipurpose glue that's corrections to the theory of	Clear, non-foaming, but still just as tough.	The all-purpose way to bond building.	Wirst strongest Grab Adhesive formula – it's crystal clear and books wirst wirst anything.	CORILIA CORILIA Strong, fast wood glue with short grip-time.	Gorila-strong instant bond,	Strong, permanent, fast and gap-filling bond. Great for multiple surface applications.	<complex-block></complex-block>
	Best for	Tough repairs on dissimilar surfaces, both indoors and out.	Transparent fixes where you don't want the glue to expand.	Tough bonds that will last, indoors or out, even underwater.	A clear, clean, extra strong bond on a wide range of construction materials.	Building, carpentry or hobby projects using wood.	Instant repairs on smaller indoor projects.	Tough repairs requiring a durable, gap filling bond.	Fabrics, crafting and more. It's repositionable & washing machine safe.
	Open Working Time	10 minutes	5 minutes	5 minutes	30 minutes	5 minutes	Not repositionable	5 minutes	Up to 4 minutes
	Grip Time	1-2 hours	2 hours	Hold for 20-60 seconds	Hold for 30-60 seconds	20-30 minutes	Hold for 10-45 seconds	30 minutes	Grips on contact
	Drying Time 100% in 24 hours	Light handling after 2 hours	Light handling after 2 hours	Light handling after 1 hour	Light handling after 2 hours	Light handling after 2 hours	Light handling after 60 seconds	Light handling after 30 minutes	Light handling after 5 minutes
	Outdoor Use	100% waterproof	Water resistant	100% waterproof	100% waterproof	D3 water resistance	Not recommended	Water resistant	100% waterproof
	Glue Expansion	Yes	None	None	None	None	None	None	None
	Dry Colour	Light brown	Clear	White	Clear	Natural wood colour	Opaque	Clear	Clear
	Finishing	Sandable, stainable	Sandable, stainable, paintable	Sandable, paintable ¹	Sandable, paintable ¹	Sandable, paintable	Sandable	Sandable, stainable, paintable ¹	Sandable, stainable, paintable
	Wood	✓	✓	✓	\checkmark	✓	✓	✓	√
	Metal	✓	✓	✓	\checkmark		✓	✓	✓
	Stone	✓	✓	✓	\checkmark			✓	✓
	Ceramic	✓	✓	✓	\checkmark		✓	✓	✓
NO	Glass	✓	√	✓	\checkmark			√	✓
JSE	Plastics ²	✓	√	✓	\checkmark		✓	√	
FOR USE ON	Brick	✓	√	✓	\checkmark		✓	√	✓
E E	Concrete	✓	✓	✓	\checkmark			✓	✓
	Foam ⁴	✓	✓		\checkmark			✓	
	Paper					✓	✓		✓
-	Rubber		√				✓		✓
	Fabric								\checkmark

¹Do not use oil-based paint ²Not suitable for polypropylene (PP) or polyethylene (PE) ³Not suitable for polystyrene (PS) ⁴Not recommended for Ethylene Vinyl Acetate (EVA) foam

GORILLA TAPE GUIDE



¹Compared to branded competitor duct tapes ²Surfaces must be clean, smooth, non-porous and water must be rubbed/pressed out from underneath tape. Not for use on applications under pressure or on seams. Overlapping tape may cause leaks. ³Application Temperature: -17°C to 93°C